

Advanced 4K x 2K video processing technology, renders up to eight videos, at the same time.

- All input and output resolutions up to 3840 x 2160.
- 8 x inputs.
- 3 x outputs.
- Composite output: Cut, crop and stack inputs, with transparent overlay.
- Low heat and power.



Perfect rendering

MIDAS II 4K can generate three video streams, each with up to 8 Mega-pixel resolution.

Input video

For each input, the MIDAS II 4K provides complete control:

- Set up any input resolution.
- Generate independent EDID (Extended Display Identification Data).
- Colour mapping.
- Transparency.

Output video

For each output, the MIDAS II 4K provides complete control:

- Set up any output resolution.
- Render a single input on a single screen.
- Create a composite of inputs in a mosaic.
- Create a composite of inputs, stacked with transparency.



Output 1



Output 2



Output 3



Safety

Thruput True-pixel graphics processing:

- Directly maps input pixel to output pixel.
- Avoids any zoom engines or pixilation chipsets.
- All data channels are isolated and data from one channel cannot pass to another.

Green solution

The MIDAS II 4K does not use any hazardous materials, and is:

- Fully RoHS compliant, with ultra-low power consumption.
- Typically 30W in normal operation.

Specification

Outputs	3 off 3840 x 2160 (DVI DL)
Inputs	8 off 3840 x 2160 (DVI DL)
Function	<ul style="list-style-type: none"> • Set input and output resolutions. • Independent EDID (Extended Display Identification Data). • Synchronise all received data. • Create composite output of any or all inputs. • Cut, crop, position and stack each input. • Map selected colours to new colours. • Set transparency colours for each input.
Power	Dual redundant, 12V 3A inputs. Mains PSU, dual external. Universal input voltage, worldwide use. Typically below 30W.
Noise	0 dB (silent operation)
MTBF	127,000 hours
Compliance	CE, FCC and ROHS.
Record	Record any output using Sentinel recorder.
HMI	Support synchronized switching with mouse & keyboard.
Extension	Up to 100m, Sentinel KVMX extender.



Thruput Limited operates a policy of continuous improvement and information in this document is subject to change without notice.

Page 2 of 2

Ref: MIDAS II 4K DN 1610-0000 V 1.2